



## FIRE DEPARTMENT FIRE PREVENTION BUREAU

Derek L. Hughes, Fire Chief David Petersen, Deputy Fire Chief Len DeJoria, Fire Prevention Officer

## Inspectors Check List Underground Storage Tank Installation

ADDRESS:	_
BUSINESS:	
#1) INSTALLATION AND LOCATION INSPECTION: Date	Inspector
6" minimum depth pea gravel beddingDead men installedFlotation Calculations submitted in lieu of deadmenAppDistance to property line or wall of any basement (3 feet minimum)Distance between tanks, shell to shell (1 foot minimum) SIZE UL# MFG. TYPE OF TANK Local 1. 2. 3. 4. 5.	•
Tank shipped under vacuumVacuum gauge reading afTank shipped under pressurePressure gauge reading afPressure/vacuum held (30 minutes minimum)	ter installation (3-5psi), or ter installation
Leak Detection System:Corrosion Protection Method:	
#2) PRODUCT LINE INSPECTION:Date	_ Inspector\
SYSTEM TYPE:Pressure, orSuction PIPING MATERIAL:FiberglassDouble Wall, or	

Flexible Piping _		Brand Name	Double Wall	
PIPING CONNECTIO	NS:			
Flexible Connect	tors where piping	connects to tank		
		ends at pump island(s)		
Flexible Connect	tors where piping	ends at vent riser(s)		
PRODUCT LINE TES		.,		
hydrostatic	PSI for	r to minutes (minimum 1	50% of max operating pressu	re)
	no visible le		1 21	
pneumatic			110% of max operating press	ure
	soap test on		1 01	
#3) TANK COVER IN3 feet of earth, or		Date	Inspector	r
8" of asphaltic co				
8 of asphatic co		concrete or		
reinforced concre				
remioreed concre	π4 Tebai 011 12	centers minimum)		
// A		_		
			Inspector	
OVERFILL PREVENT				
audible and visua		ll, or		
automatic shut-o				
reduced flow rat		hut-off device		
EMERGENCY SHUT-				
		nearer than 25 feet to any		
	dicating location of	of switch to read "EMER	GENCY FUEL SHUTDOWN	N
DEVICE"				
VENT PIPE(S):				
Not less than 1-1/4				
5 feet from building		rty line		
8feet above fill pip				
12 feet above adja				
DISPENSER ISLAND				
_				
Nozzle Make and Mod				_
		wedNot Allo	wed	
Leak Containment				
			ich the dispenser is mounted	
		ed flush with top surface	or dispenser mount	
	island elevated at			
			filled on 4'centers minimum),	
_	_		d (attach description to form)	
		of all dispenser islands		
		property lines or any bu		
	•	oes not reach within 5' o	f any building opening	
No smoking signs				
Shut off Motor W	hile fueling signs			

No filling of Unapproved Containers signs
Fire Extinguisher(s) of minimum 2-A,20-B:C located not more than 75' from any pump, dispenser,
or fill-pipe opening
COMMUNICATIONS:
Intercom system operational, allowing two-way communication form each island to the attendant
Telephone working to dial 911 (without coin required) in case of emergency
SAFETY RULES:
Owner notified annual tests required of all leak-detecting devices, with results maintained on
premises
Owner notified accurate daily inventory records shall be maintained and kept on premises
STORAGE AND USE PERMIT ISSUED:
NO:
DATE:
INSPECTOR: